

Plastic square shape inductive sensors **LE50** series


## Features

- ◆ Non contact detection, safe and reliable;
- ◆ ASIC design;
- ◆ Perfect choice for metallic targets detection;




## Part number

NPN NO	LE50SF05DNO	LE50SN08DNO	PNP NO	LE50SF05DPO	LE50SN08DPO
NPN NC	LE50SF05DNC	LE50SN08DNC	PNP NC	LE50SF05DPC	LE50SN08DPC

## Technical specifications

Mounting	Flush	Non-flush	Leakage current [I <sub>r</sub> ]	≤10mA	
Rated distance [S <sub>n</sub> ]	5mm	8mm	Circuit protection	Short-circuit, overload and reverse polarity	
Assured distance [S <sub>a</sub> ]	0...4mm	0...6.4mm	Output indicator	Yellow LED	
Dimensions	10 *25 *50 mm		Ambient temperature	-25°C...70°C	
Output	NO/NC(depends on part number)		Ambient humidity	35-95%RH	
Supply voltage	10...30 VDC		Switching frequency [F]	700 Hz	500Hz
Standard target	Fe 25*25*1t	Fe 25*25*1t	Voltage withstand	1000V/AC 50/60Hz 60s	
Switch-point drifts [%/Sr]	≤± 10%		Insulation resistance	≥50MΩ(500VDC)	
Hysteresis range [%/Sr]	1...20%		Vibration resistance	10...50Hz (1.5mm)	
Repeat accuracy [R]	≤3%		Degree of protection	IP67	
Load current	≤200mA		Housing material	PBT	
Residual voltage	≤2.5V		Connection type	2m PVC cable	

## Dimensions



## Wiring diagram

